

## Mantis 38 Tracked Narrow Access Platform



## Mantis 38 metre Tracked

## Technical Specification: Maximum Working Height: 38 m 125' Platform Height: 119' 0" 36.27 m Horizontal Outreach: 50' 0" (approx) 15 m Rotating Cage size: 0.89 m x 2.41 m 2' 11" x 7' 11" (2-man) (1-man) 0.78 m x 0.78 m 2' 6" x 2' 6" Min stowed width without cage: 5 1.7 m 8′ 2 Stowed height: 2.470 m Stowed length: 24′ 4 7.4 m Track contact area: 1.95 m 6' 5" **Gross Weight:** 9360 kgs


Maximum weight on any one outrigter#2.3 Kilonewtons Safe Working Load: 200/120kgs

Cage rotation: 150°
Turntable continuous slewing: 360°
Track lengths: 2.5 m 8'
Ground clearance between tracks 300 mm
Maximum slope: 40%

Maximum permissible wind speed:

Power: 240v A.C. and 380/415v 3 phase Electric Hatz "Silent Pack" Diesel engine (1500 rpm)

NB: For faster mains operation 3 phase power is recommended.
\*Note outreach varies according to jack-spread & cage loading.
† When cage & Boom are fully extended over that outrigger.
E & OE. Constant engineering progress makes it necessary that we reserve the right to vary specifications, equipment and pricing policy without notice.



## Mantis 38 Tracked Triple Power

- 38 m. (125') maximum Working Height
  15 m. (50') maximum Outreach
  1.7 m. (5' 7") minimum Machine-width
- 1.7 m. (5' 7") minimum Machine-width3.9 m. (12' 10") minimum Jack-width
- An On-Board Generator powers your hand tools direct from a socket in the cage, (ask us for the voltage you need).
- Special narrow 1-man cage of 0.78 m x 0.78 m for restricted working areas is available.
- Large 2.41 m x 0.89 m rotating cage is available for maximum working interface.
- Numerous stabiliser leg configurations allow best use of irregular or restricted floor space.
- Stabiliser legs can be set up on uneven ground even on steps.
- Rubber based jack feet pads offer protection to flooring.
   Self propelled, pedestrian controlled inch perfect positioning
- seir propelled, pedestrian controlled inch perfect positioning through individual track control.
- Triple power mains electric 240v or 380/415v 3 phase or Hatz "Silent Pack" diesel.
- Fully Certificated and recognised Training on the safe operation of these machines is available through Facelift, Call the Training Department 01444 881166

